

SHIPPING INFORMATION



Reel Size Charts / Length Policy

AirCell® Shipping Information (Revision 5/6/10)

AirCell® Radiating Cable Weight/Length Per Pack - 50 & 75 Ohm

			Carton, Qty, Ft		Reel, Qty, Ft				
Cable Size	Product Code	Cable Weight (lb/ft)	38"x38"x7"	24"D x 12"W	24"D x 17"W	30"D x 15"W	33"D x 21"W	42"D x 30"W	
1/2"	AR012J50 / 75	0.119 / .097	5-500	100-430	431-750	751-1200	1201-2000	2001-5500	
	AR012FX50 / 75	0.125 / .103	5-500	100-430	431-750	751-1200	1201-2000	2001-5500	
	AR012F50 / 75	0.138 / .116	5-500	100-430	431-750	751-1200	1201-2000	2001-5500	
	AR012R50 / 75	0.176 / .155	5-500	100-430	431-750	751-1200	1201-2000	2001-5500	
Tare Weight, lb	-	-	9	12	13	23	36	96	
			Carton, Qty, Ft		Reel, Qty, Ft				
Cable Size	Product Code	Cable Weight (lb/ft)	38"x38"x7"	46"x46"x9"	48"D x 18"W	48"D x 30"W	54"D x 30"W	58"D x 40"W	
5/8"	AR058J50 / 75	0.235 / .179	5-250	251-400	401-2000	2001-3000	3001-4500	-	
	AR058FX50 / 75	0.244 / .188	5-250	251-400	401-2000	2001-3000	3001-4500	-	
	AR058R50 / 75	0.315 / .259	5-250	251-400	401-2000	2001-3000	3001-4500	-	
7/8"	AR078J50 / 75	0.295 / .289	-	5-330	331-1100	1101-1800	1801-2400	2401-3000	
	AR078FX50 / 75	0.306 / .302	-	5-330	331-1100	1101-1800	1801-2400	2401-3000	
	AR078R50 / 75	0.400 / .395	-	5-330	331-1100	1101-1800	1801-2400	2401-3000	
Tare Weight, lb	-	-	9	12	75	143	165	332	
			Reel, Qty, Ft						
Cable Size	Product Code	Cable Weight (lb/ft)	62"D x 23"W	72"D x 23"W	72"D x 29"W	72"D x 42"W	76"D x 42"W	80"D x 42"W	
1-1/4"	AR114J50	0.531	100-650	651-1000	1001-1600	1601-2300	2301-3100	3101-3500	
	AR114FX50	0.548	100-650	651-1000	1001-1600	1601-2300	2301-3100	3101-3500	
	AR114R50	0.685	100-650	651-1000	1001-1600	1601-2300	2301-3100	3101-3500	
1-5/8"	AR158J50	0.675	100-400	401-750	751-1000	1001-1550	1551-1900	1901-2200	
	AR158FX50	0.793	100-400	401-750	751-1000	1001-1550	1551-1900	1901-2200	
	AR158R50	0.961	100-400	401-750	751-1000	1001-1550	1551-1900	1901-2200	
Tare Weight, lb	-	-	270	285	330	368	447	470	

Special Conditions for Fire Retardant Jacket (FX, F, R type of jacket) for AirCell Transline & Radiating Cable

Due to the complex manufacturing process of fully bonded air dielectric cable, Trilogy does not have standard length for in building cable with fire retardant jackets. Trilogy will fill customer orders with any combination of existing random length available. Thus, billed footage could vary up to +/- 10% with the total ordered quantity and +/- 20% per reel tolerance.

For any specific exact length requirement per reel (without 20% tolerance per reel), or minimum length per reel requirements, additional length Premiums will be charged as following:

10% premium charge: for exact length per reel or a minimum length is over 1,000 feet per reel for 1-1/4" and 1-5/8"

20% premium charge: for exact length per reel or a minimum length is over 1,500 feet per reel for 1-1/4" size and 1-5/8" (accepted maximum length is 2,000 feet).

Phone: 1-800-TRIOLOGY
 1-601-932-4461
 Fax: 1-601-939-6637



Website: www.trilogycoax.com
 Address: 2910 HWY 80 East
 Pearl, MS 39208 U.S.A.