



AirCell® Shipping Information (Revision 5/10/11)

AirCell® coaxial cables are shipped in cartons or on wooden reels. All reels are disposable. Small reels (under 62") are protected by use of heavy-duty cardboard or bubble wrap. Large reels (62" and above) for 7/8" and 1-5/8" size cable are protected by wrapping them with plywood.

The tables below show the weight/length of cables shipped in cartons or disposable wooden reels.

Shipping information is subject to change without notice. For current information, contact Trilogy Communications.

AirCell® Transline Cable Weight/Length Per Pack - 50 & 75 Ohm

| | | | Carton, Qty, Ft | | Reel, Qty, Ft | | | |
|-----------------|----------------|----------------------|-----------------|-------------|---------------|-------------|-------------|--|
| Cable Size | Product Code | Cable Weight (lb/ft) | 38"x38"x7" | 24"D x 12"W | 24"D x 17"W | 30"D x 15"W | 33"D x 21"W | |
| 1/2" | AT012J50 / 75 | 0.127 / .104 | 5-500 | 100-430 | 431-750 | 751-1200 | 1201-2000 | |
| | AT012FX50 / 75 | 0.133 / .110 | 5-500 | 100-430 | 431-750 | 751-1200 | 1201-2000 | |
| | AT012F50 / 75 | 0.141 / .116 | 5-500 | 100-430 | 431-750 | 751-1200 | 1201-2000 | |
| | AT012FV50 | 0.138 | 5-500 | 100-430 | 431-750 | 751-1200 | 1201-2000 | |
| | AT012R50 / 75 | 0.181 / .156 | 5-500 | 100-430 | 431-750 | 751-1200 | 1201-2000 | |
| Tare Weight, lb | - | - | 9 | 12 | 13 | 23 | 36 | |
| | | | Carton, Qty, Ft | | Reel, Qty, Ft | | | |
| Cable Size | Product Code | Cable Weight (lb/ft) | 38"x38"x7" | 46"x46"x9" | 48"D x 18"W | 48"D x 30"W | 54"D x 30"W | |
| 5/8" | AT058J50 / 75 | 0.250 / .200 | 5-250 | 251-400 | 401-2000 | 2001-3000 | 3001-4500 | |
| | AT058FX50 / 75 | 0.257 / .208 | 5-250 | 251-400 | 401-2000 | 2001-3000 | 3001-4500 | |
| | AT058FV50 | 0.264 | 5-250 | 251-400 | 401-2000 | 2001-3000 | 3001-4500 | |
| | AT058R50 / 75 | 0.328 / .274 | 5-250 | 251-400 | 401-2000 | 2001-3000 | 3001-4500 | |
| 7/8" | AT078J50 / 75 | 0.299 / .316 | - | 5-330 | 331-1100 | 1101-1800 | 1801-2400 | |
| | AT078FX50 / 75 | 0.322 / .328 | - | 5-330 | 331-1100 | 1101-1800 | 1801-2400 | |
| | AT078FV50 | 0.331 | - | 5-330 | 331-1100 | 1101-1800 | 1801-2400 | |
| | AT078R50 / 75 | 0.415 / .430 | - | 5-330 | 331-1100 | 1101-1800 | 1801-2400 | |
| Tare Weight, lb | - | - | 9 | 12 | 75 | 143 | 165 | |
| | | | Reel, Qty, Ft | | | | | |
| Cable Size | Product Code | Cable Weight (lb/ft) | 62"D x 23"W | 72"D x 23"W | 72"D x 29"W | 72"D x 42"W | 76"D x 42"W | |
| 1-1/4" | AT114J50 | 0.555 | 100-650 | 651-1000 | 1001-1600 | 1601-2300 | 2301-3100 | |
| | AT114FX50 | 0.527 | 100-650 | 651-1000 | 1001-1600 | 1601-2300 | 2301-3100 | |
| | AT114FV50 | 0.541 | 100-650 | 651-1000 | 1001-1600 | 1601-2300 | 2301-3100 | |
| | AT114R50 | 0.708 | 100-650 | 651-1000 | 1001-1600 | 1601-2300 | 2301-3100 | |
| 1-5/8" | AT158J50 | 0.701 | 100-400 | 401-750 | 751-1000 | 1001-1550 | 1551-1900 | |
| | AT158FX50 | 0.822 | 100-400 | 401-750 | 751-1000 | 1001-1550 | 1551-1900 | |
| | AT158FV50 | 0.838 | 100-400 | 401-750 | 751-1000 | 1001-1550 | 1551-1900 | |
| | AT158R50 | 0.990 | 100-400 | 401-750 | 751-1000 | 1001-1550 | 1551-1900 | |
| Tare Weight, lb | - | - | 270 | 285 | 330 | 368 | 447 | |

AirCell® Transline Cable with Regular Jacket (J)

Invoice quantity is based on ordered footage. Actual length can be +/- 1%. No additional surcharge will be assessed if the customer will take multiple lengths on a reel or any combination of cable lengths per reel (or bulk reel). Any specific tower length requested on individual reels will be assessed with a \$100 surcharge per reel.

AirCell® Transline Fire Retardant Jacket (FX, F, FV, R type of jacket)

See next page.